

Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600212

· Trade name: Gloss top coat E-COLL

· Article number: 4317784664233

· UFI: 3AYX-0QEJ-Y908-DPCY

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture

Paint

Coating material

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

· Further information obtainable from: Product safety department

· 1.4 Emergency telephone number: Giftinformationszentrum Mainz - Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The labelling of an aspiration hazard (Asp.Tox.1 H304) is not required for aerosol dispensers and containers with a sealed spray device (Regulation (EC) 1272/2008, Annex 1,1.3.3).

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 1)

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone n-butyl acetate ethyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

Contd. of page 2

	(Con	td. of page 2)
Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx		2.5-10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059		2.5-10%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	<1.25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Personal protection for the First Aider.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 4)

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

CAS: 123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm

Long-term value: 241 mg/m³, 50 ppm

CAS: 141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm

Long-term value: 734 mg/m³, 200 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Respiratory protection: Self-contained respiratory protective device.
- · Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)




Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 5)

· Eye/face protection



Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical stateColour:Odour:AerosolBlackCharacteristic

Odour threshold:
 Melting point/freezing point:
 Not determined.
 Undetermined.

· Boiling point or initial boiling point and boiling

range 55.8-56.6 °C (CAS: 67-64-1 acetone)
• Flammability Extremely flammable aerosol.

· Lower and upper explosion limit

Lower: 2.2 Vol %Upper: 15 Vol %

• Flash point: -97 °C (CAS: 74-98-6 propane)

· Auto-ignition temperature: 415 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

Dynamic: Not determined.Solubility

water: Fully miscible.
 Partition coefficient n-octanol/water (log value)
 Not determined.

• Vapour pressure at 20 °C: 4,200 hPa (CAS: 74-98-6 propane)

· Vapour pressure at 50 °C: 800 hPa

Density and/or relative density

Density at 20 °C: 0.7121-0.7199 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

• Organic solvents: 56.0 % • VOC (EC) % 56.00 %

(Contd. on page 7)



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 6)

· **VOC (EC) g/l** 398.8-403.1 g/l

· Solids content: 0.0 %

· Change in condition

• Evaporation rate Not applicable.

Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

Aerosols
 Extremely flammable aerosol. Pressurised container:

May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void Void · Desensitised explosives

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- \cdot 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 7)

		(Conta. or page 1)		
· LD/LC50 v	· LD/LC50 values relevant for classification:			
CAS: 106-97-8 butane, pure				
Inhalative	LC50/4h	658 ppm (rat)		
CAS: 67-64-1 acetone				
Oral	LD50	5,800 mg/kg (rat)		
Dermal	LD50	20,000 mg/kg (rabbit)		
Inhalative	LC50/4h	76 mg/m³ (rat)		
CAS: 74-98-6 propane				
Inhalative	LC50/4h	>20 mg/m³ (rat)		
CAS: 123-86-4 n-butyl acetate				
Oral	LD50	13,100 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4h	>21 ppm (rat)		
CAS: 141-	CAS: 141-78-6 ethyl acetate			
Oral	LD50	5,620 mg/kg (rabbit)		
Inhalative	LC50/4h	1,600 ppm (rat)		

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- $\cdot \, \textbf{STOT-repeated exposure} \, \text{Based on available data, the classification criteria are not met.} \\$
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
CAS: 67-64-1 acetone		
LC50 (96h)	5,000 mg/L (Lepomis macrochirus)	
LC50/48h	8,800 mg/l (Daphnia magna)	
NOEC	430 mg/l (algae)	
NOEC/16h	1,700 mg/l (Pseudomonas putida)	
	(Contd. on page 0)	

(Contd. on page 9)



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

NOEC/48h 4,740 mg/l (Pseudokirchneriella subcapitata)
96h LC50 5,540 mg/l (Oncorhynchus mykiss)

CAS: 123-86-4 n-butyl acetate

LC50 (96h) 18 mg/L (Pimephales promelas)
EC50 (48h) 44 mg/L (Daphnia magna)
EC50/24h 73 mg/l (Daphnia magna)
EC50/72h 647.7 mg/l (S)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue		
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST	
16 05 00	gases in pressure containers and discarded chemicals	
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	
HP3	Flammable	

Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · ADR UN1950 AEROSOLS



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 9)

·IMDG **AEROSOLS**

·IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



2 5F Gases. · Class

· Label 2.1

· IMDG, IATA



2.1 Gases. · Class

· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user

· Hazard identification number (Kemler code):

· EMS Number:

· Stowage Code

F-D,S-U SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS:

Category C, Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1

litre:

Warning: Gases.

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

(Contd. on page 11)



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 10)

Transport categoryTunnel restriction code

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone

n-butyl acetate

ethyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

- Named dangerous substances ANNEX I Methanol
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 11)

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

CAS: 67-64-1 acetone

3

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 67-64-1 acetone 3

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: sdb@ede.de

· Date of previous version: 27.06.2023

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative



Printing date 27.06.2023 Version number 301 Revision: 27.06.2023

Trade name: Gloss top coat E-COLL

(Contd. of page 12)

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

 \cdot * Data compared to the previous version altered.

EU —